



## The 360° Classic

### 4-way standard cassette



#### Highlights

- Outstanding efficiency
- Two panels available for selection
- External fresh air supply possible



4-way standard cassette for combination with VRF outdoor units from the MiNi-SMMS-e, SMMS-e, and SHRM-e model series. Customized comfort, even for large spaces with high power requirements. Available in ten power levels from 2.8 to 16.0 kW.



#### Performance

- Very high energy efficiency
- Exhaust panel available for wide or direct air flow
- High-performance heat exchanger
- Self-cleaning function
- Low-noise, 3-stage fan
- Quiet function
- Auto diagnostic system



#### Flexibility

- Optimal air distribution, even in high spaces
- Easy-to-remove, washable dust filter
- Optional WiFi control via smartphone, tablet, or PC



#### Technical details

- External fresh air supply possible up to 15% of the nominal airflow
- Integrated drain pump with a discharge head up to 85 cm
- Receiver for infrared remote control can be integrated
- Can be combined with all cable remote controls
- Additional functions available with the RBC-AMS54E-ES remote control
- Automatic restart setting after power outage

## 4-way standard cassette

Technical data			MMU-AP0484HP1-E
Cooling capacity	kW	❄️	14,00
Power consumption (min./nom./max.)	kW	❄️	0,112
Heating capacity	kW	🔥	16,00
Airflow	m <sup>3</sup> /h		1130/1430/2130
Sound pressure level (low/med/high)	dB(A)	❄️	33/38/46
Liquid pipe diameter	mm (inch)		9,5 (3/8)
Suction gas pipe diameter	mm (inch)		15,9 (5/8)
Condensate pipe diameter	mm		VP25 (25/32)
Power supply	V/Ph+N/Hz		220-240/1/50
Running current	A	❄️	0,88
Refrigerant			R410A
Dimensions (HxWxD)	mm		319 x 840 x 840
Weight	kg		25
Panel dimensions (HxWxD)	mm		30 x 950 x 950
Panel weight	kg		4

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <http://www.toshiba-klima.at/en/measuring-conditions.html>



**Energy Label:** Energy label **A+ to A+++**, indicates the power consumption and energy efficiency class.



**HI POWER:** Particularly strong airflow for quickly reaching the requested temperature.



**ErP Ecodesign:** All criteria of **ECODESIGN**-guideline are fulfilled and confirm highest system efficiency.



**Auto diagnostic:** Check of system for flawless operation.



**Hybrid inverter control:** Smooth capacity regulation.



**Eco Mode:** Energy saving function.



**Rotary compressor:** Reliability and high efficiency.



**Quiet Mode:** Particularly low noise level - whispering mode.



**Twin rotary compressor:** Long-lasting, smoothly running and highest efficiency.



**Comfort Sleep:** Gradual increase of temperature by 2 °C until morning.



**R410A:** Used refrigerant: R410A.



**Power Selection:** Capacity regulation and therefore power savings of up to 25, 50 or 75%.



**R32:** Used refrigerant: R32.



**Floor Mode:** Natural floor warming effect for greater comfort.



**Wifi ready:** Optional control of the system via a smartphone.



**Preset Mode:** Activates individual settings at the touch of a button.



**KNX:** Optional KNX bus connection.



**One Touch Mode:** Fully automatic operation adapted to your needs.



**Dust filter:** Washable filter against coarse contamination.



**Timer:** Individual programming of on-/off times.



**IAQ filter:** Fine mesh filter with natural substances.



**Off Timer:** Shutdown of the unit at chosen times (30 min to 12 h).



**Active carbon-catechin filter:** Cleansing filter with enzymes from green tea.



**Week Timer:** Up to four settings per day and seven per week.



**Plasma filter: Pure Mode:** Electrostatic filter system.



**Automatic Restart:** After a power blackout.



**Air ionizer:** Negative ions cover polluted particles in the air. Dust, pollen and smoke are neutralized.



**8 °C frost protection function:** Frost protection for uninhabited rooms.



**Self-cleaning function:** Usage of condensate water for cleaning.



**Louver:** Flexible setting of louvers.



**Auto Mode:** Automatic selection between cooling and heating.



**3D Airflow:** 6 different airflow patterns in all directions.