



Perfect ambiance

Ceiling unit



Highlights

- Attractive design
- Low noise level
- Optimal air distribution in cooling & heating mode



Under ceiling unit for combination with VRF outdoor units from the MiNi-SMMS-e, SMMS-e, and SHRM-e model series. Elegant design with rounded edges and a large air control fin for optimal air circulation. Available in seven power levels from 4.5 to 16.0 kW.



Performance

- Very high energy efficiency
- Optimal temperature distribution right down to the floor in heating mode
- High-performance heat exchanger
- Self-cleaning function
- Low-noise, 3-stage fan
- Quiet function
- Auto diagnostic system



Technical details

- Easy installation via removable suspension fixtures
- TCB-DP31CE drain pump optionally available
- Receiver for infrared remote control can be integrated
- Can be combined with all cable remote controls
- Additional functions available with the RBC-AMS54E-ES remote control
- Automatic restart setting after power outage



Flexibility

- Optimal air distribution, even in high spaces
- Easy-to-remove, washable dust filters
- Additional boards available for external analog & digital control
- Optional WiFi control via smartphone, tablet, or PC

Ceiling unit

| Technical data | | | MMC-AP0188HP-E |
|-------------------------------------|-------------------|----|-----------------|
| Cooling capacity | kW | ❄️ | 5,60 |
| Power consumption (min./nom./max.) | kW | ❄️ | 0,034 |
| Heating capacity | kW | 🔥 | 6,30 |
| Power consumption (min./nom./max.) | kW | 🔥 | 0,034 |
| Airflow | m ³ /h | | 540/720/960 |
| Sound pressure level (low/med/high) | dB(A) | ❄️ | 28/35/37 |
| Sound pressure level (low/med/high) | dB(A) | 🔥 | 28/35/37 |
| Liquid pipe diameter | mm (inch) | | 6,4 (¼) |
| Suction gas pipe diameter | mm (inch) | | 12,7 (½) |
| Condensate pipe diameter | mm | | VP20 (20/26) |
| Power supply | V/Ph+N/Hz | | 220-240/1/50 |
| Running current | A | ❄️ | 0,37 |
| Running current | A | 🔥 | 0,37 |
| Running current (nom.) | A | | 0,37 |
| Current consumption (nom.) | A | | 0,37 |
| Refrigerant | | | R410A |
| Dimensions (HxWxD) | mm | | 235 x 950 x 690 |
| Weight | kg | | 24 |

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <http://www.toshiba-klima.at/en/measuring-conditions.html>



Energy Label: Energy label **A+ to A+++**, indicates the power consumption and energy efficiency class.



HI POWER: Particularly strong airflow for quickly reaching the requested temperature.



ErP Ecodesign: All criteria of **ECODESIGN**-guideline are fulfilled and confirm highest system efficiency.



Auto diagnostic: Check of system for flawless operation.



Hybrid inverter control: Smooth capacity regulation.



Eco Mode: Energy saving function.



Rotary compressor: Reliability and high efficiency.



Quiet Mode: Particularly low noise level - whispering mode.



Twin rotary compressor: Long-lasting, smoothly running and highest efficiency.



Comfort Sleep: Gradual increase of temperature by 2 °C until morning.



R410A: Used refrigerant: R410A.



Power Selection: Capacity regulation and therefore power savings of up to 25, 50 or 75%.



R32: Used refrigerant: R32.



Floor Mode: Natural floor warming effect for greater comfort.



Wifi ready: Optional control of the system via a smartphone.



Preset Mode: Activates individual settings at the touch of a button.



KNX: Optional KNX bus connection.



One Touch Mode: Fully automatic operation adapted to your needs.



Dust filter: Washable filter against coarse contamination.



Timer: Individual programming of on-/off times.



IAQ filter: Fine mesh filter with natural substances.



Off Timer: Shutdown of the unit at chosen times (30 min to 12 h).



Active carbon-catechin filter: Cleansing filter with enzymes from green tea.



Week Timer: Up to four settings per day and seven per week.



Plasma filter: Pure Mode: Electrostatic filter system.



Automatic Restart: After a power blackout.



Air ionizer: Negative ions cover polluted particles in the air. Dust, pollen and smoke are neutralized.



8 °C frost protection function: Frost protection for uninhabited rooms.



Self-cleaning function: Usage of condensate water for cleaning.



Louver: Flexible setting of louvers.



Auto Mode: Automatic selection between cooling and heating.



3D Airflow: 6 different airflow patterns in all directions.