



FOR FRESH AIR PRECONDITIONING

Fresh-air duct unit SMMSu



Highlights

- Perfect solution for additional inflow of fresh air
- Pre-heating and pre-cooling function
- Can be used in combination with other VRF indoor units

Fresh-air duct unit for combination with VRF outdoor units from the SMMS-e and SMMS-u model series (sizes 112 and 128 for SMMS-u only). Pre-heating or cooling function in combination with other indoor units. Available in five capacity levels from 14.0 to 40.0 kW.



Performance

- High energy efficiency
- Can be integrated unseen into false ceilings
- Self-cleaning function
- Low-noise 5-step fan
- External, static pressure can be set up to 200 Pa
- Auto diagnostic system



Flexibility

- 100% fresh air processing
- Can be regulated from +16 to +27°C in cooling and heating mode
- Wide operating range: air-intake temperatures from -10°C to +46°C
- Can be realized with up to 30% of total system output
- Up to two units can be connected in the system
- Diversity from 80% to 110%



Technical details

- Air intake from behind
- Customized external air filter settings
- TCB-DP40DFP-E drain pump optionally available
- External receiver kit for infrared remote control possible
- Can be combined with all cable remote controls
- Cannot be combined with VN-HEXE or hot water module
- Automatic restart after power blackout adjustable

Fresh-air duct unit SMMSu

| Technical data | | | MMD-UP1281HFP-E |
|---|-------------------|----|-------------------------------|
| Capacity code | HP | | 14 |
| Cooling capacity | kW | ❄️ | 40,00 |
| Power consumption (min./nom./max.) | kW | ❄️ | 0,330 |
| Heating capacity | kW | 🔥 | 25,20 |
| Power consumption (min./nom./max.) | kW | 🔥 | 0,330 |
| Airflow | m ³ /h | | 2130/2580/3060 |
| External static pressure | Pa | | 50/75/100/125/ 150/175/200 |
| Sound pressure level (low/med/high) | dB(A) | ❄️ | 35/37/38/40/42 |
| Sound pressure level (low/med/high) | dB(A) | 🔥 | 35/37/38/40/42 |
| Liquid pipe diameter | mm (inch) | | 15,9 (5/8) |
| Suction gas pipe diameter | mm (inch) | | 28,6 (1 1/8) |
| Condensate pipe diameter | mm | | VP25 (25/32) |
| Power supply | V/Ph+N/Hz | | 220-240/1/50 |
| Running current | A | ❄️ | 1,83 |
| Running current | A | 🔥 | 1,83 |
| Current consumption (nom.) | A | | 1,91 |
| Outdoor temperature operating range (min.-max.) | °C | ❄️ | +5 / +46 |
| Outdoor temperature operating range (min.-max.) | °C | 🔥 | -10 / +46 |
| Refrigerant | | | R410A |
| Dimensions (HxWxD) | mm | | 477 x 1430 x 900 |
| Weight | kg | | 99 |

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <http://www.toshiba-klima.at/en/measuring-conditions.html>



Energy Label: Energy label **A+ to A+++**, indicates the power consumption and energy efficiency class.



HI POWER: Particularly strong airflow for quickly reaching the requested temperature.



ErP Ecodesign: All criteria of **ECODESIGN**-guideline are fulfilled and confirm highest system efficiency.



Auto diagnostic: Check of system for flawless operation.



Hybrid inverter control: Smooth capacity regulation.



Eco Mode: Energy saving function.



Rotary compressor: Reliability and high efficiency.



Quiet Mode: Particularly low noise level - whispering mode.



Twin rotary compressor: Long-lasting, smoothly running and highest efficiency.



Comfort Sleep: Gradual increase of temperature by 2 °C until morning.



R410A: Used refrigerant: R410A.



Power Selection: Capacity regulation and therefore power savings of up to 25, 50 or 75%.



R32: Used refrigerant: R32.



Floor Mode: Natural floor warming effect for greater comfort.



Wifi ready: Optional control of the system via a smartphone.



Preset Mode: Activates individual settings at the touch of a button.



KNX: Optional KNX bus connection.



One Touch Mode: Fully automatic operation adapted to your needs.



Dust filter: Washable filter against coarse contamination.



Timer: Individual programming of on-/off times.



IAQ filter: Fine mesh filter with natural substances.



Off Timer: Shutdown of the unit at chosen times (30 min to 12 h).



Active carbon-catechin filter: Cleansing filter with enzymes from green tea.



Week Timer: Up to four settings per day and seven per week.



Plasma filter: Pure Mode: Electrostatic filter system.



Automatic Restart: After a power blackout.



Air ionizer: Negative ions cover polluted particles in the air. Dust, pollen and smoke are neutralized.



8 °C frost protection function: Frost protection for uninhabited rooms.



Self-cleaning function: Usage of condensate water for cleaning.



Louver: Flexible setting of louvers.



Auto Mode: Automatic selection between cooling and heating.



3D Airflow: 6 different airflow patterns in all directions.